



ADCRYL AP 5055 Acrylic Solvent Pressure Sensitive Adhesive

A premium quality, high viscosity, acrylic solvent based pressure sensitive adhesive, which gives outstanding shear properties along with excellent peel and tack.

[Technical Data Sheet](#)

| | |
|--|--|
| Chemical Composition | Vinyl Acrylic Co Polymer |
| Physical Appearance | Clear transparent viscous solution |
| Solid Content | 50 ± 2 % |
| Viscosity at 25°C by RVD11+ Sp. No. 5 / 10rpm | 50 to 70 poise |
| Peel Adhesion at 33 gsm | 1.8 to 2 kgs |
| Diluents | Ethyl Acetate, Toluene, etc |
| Application Method | Roller (Direct or Reverse) |
| Type | Aggressive thermoplastic |
| Recommended Uses | Specialty self adhesive tapes, DS tapes, etc |
| Storage Life | 5 to 6 months (under standard conditions) |
| Packing | 200 Kgs nett. |

(The above specifications are subject to change. The information in this bulletin is based on data believed to be reliable and is given in good faith. However due to variation in storage, handling, equipments and other factors beyond our control, we do not guarantee the result to be obtained nor do we assume any liability in this respect.)

Rev No.1 dtd 7th, July, 2009